

HP10S

Helical Rotor Pump Range



Description:

Positive Displacement pumps, also known as "Progressive Cavity" or "Screw Pumps". Pumping element consists of a metal rotor within a rubber stator.

Applications:

Water Jetting, hydropower generation, agricultural, mine dewatering, mine slurry movement, food and beverage, chemical dosing, gland flushing, water and waste water, environmental waste, chemical and pharmaceutical.

Advantages:

Ability to pump most fluids, including caustic, abrasive and viscous product. Continuous non pulsating flow. Does not churn or shear product, ideal for shear sensitive fluids. Can pump fluids at high temperatures. Ability to handle hard or soft solids in suspension. Wide selection of materials available, including food grade, to suit various applications.



+2711 618 2003



+2711 618 3138





sales@cemo.co.za



www.cemo.co.za

Crown Building, 64 Hanau Street, Wolhuter, Johannesburg, South Africa
P O Box 27023, Jeppestown, 2043, South Africa



Data supplied may vary as required



Average Performance			Pump: HP10S	
Max 1500 rpm	Max DIFF Pressure	750 kPa	Inlet Diameter	40 mm
Rotation: Anti-Clockwise	Min Starting Torque	6 N.m	Outlet Diameter	40 mm
Tested on water at 20 °C				

Data supplied may vary as required



+2711 618 2003



+2711 618 3138



sales@cemo.co.za



www.cemo.co.za

Crown Building, 64 Hanau Street, Wolhuter, Johannesburg, South Africa

P O Box 27023, Jeppestown, 2043, South Africa